

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE3 Three-Phase

Product code : 14352815

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/
T125 °C

Catalog # : E20018ET3YAX355MLF3W

Frame : 355M/L
Output : 200 kW (270 HP)
Poles : 4
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 367/211 A
L. R. Amperes : 2202/1268 A
LRC : 6.0
No load current : 105/60.5 A
Rated speed : 1490 rpm
Slip : 0.67 %
Rated torque : 946 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 220 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 166 sq.ft.lb
Design : N

Locked rotor time : 39s (cold) 22s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 76.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 3297 lb

Output	25%		50%		75%		100%	
Efficiency (%)	95.6	95.6	95.8	95.8	96.0	96.0	96.2	96.2
	95.6	94.5	95.8	95.0	96.2	95.8	96.3	96.2
Power Factor	0.52	0.48	0.75	0.72	0.83	0.81	0.86	0.85
	0.45	0.47	0.69	0.71	0.79	0.80	0.84	0.84

Foundation loads
Max. traction : 2752 lb
Max. compression : 6049 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	4.0	4.0	3.9	4.0
	P2 (0,5;1,0)	2.9	2.9	2.9	2.9
	P3 (0,25;1,0)	2.4	2.4	2.4	2.4
	P4 (0,9;0,5)	2.4	2.4	2.3	2.4
	P5 (0,5;0,5)	1.4	1.4	1.4	1.4
	P6 (0,5;0,25)	1.1	1.1	1.0	1.1
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6322 C3	6319 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	9000 h	11000 h
Lubricant amount	:	60 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

ATEX
Baseefa 10ATEX0192X
BAS21UKEX0284X
II 3G Ex ec IIC T3 Gc
II 3D Ex tc IIIB T125°C Dc
EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
ООО «НАННО ЛЦБЭ»
IECEX
IECEX BAS 10.0099X

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	27/03/2024			
		Revision		

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	27/03/2024			