## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer Product line : ODP High Efficiency Three-Phase Product code: 12407800 Catalog #: 02536OP3VFP256TC Frame : 256TC Locked rotor time : 18s (cold) 10s (hot) Output : 25 HP (18.5 kW) Temperature rise : 105 K Poles Duty cycle : Cont.(S1) : 2 Frequency : 60 Hz Ambient temperature : -20°C to +40°C Rated voltage : 200/400 V Altitude : 1000 m.a.s.l. Rated current : 67.4/33.7 A Protection degree : IP23 : IC01 - ODP L. R. Amperes : 404/202 A Cooling method **LRC** : 6.0x(Code G) Mounting : F-1 : Both (CW and CCW) No load current : 21.6/10.8 A Rotation<sup>1</sup> Rated speed : 3530 rpm Noise level<sup>2</sup> : 67.0 dB(A) Slip : 1.94 % Starting method : Direct On Line Rated torque : 37.2 ft.lb Approx. weight<sup>3</sup> : 231 lb Locked rotor torque : 200 % Breakdown torque : 250 % : F Insulation class Service factor : 1.15 Moment of inertia (J) : 0.9774 sq.ft.lb Design 25% 50% Output 75% 100% Foundation loads Efficiency (%) 90.0 90.2 91.0 91.0 Max. traction : 330 lb Power Factor : 561 lb 0.51 0.76 0.84 0.87 Max. compression Non drive end Drive end 6309 Z C3 Bearing type 6209 Z C3 Without Bearing Seal Without Bearing Seal Sealing 20000 h Lubrication interval 20000 h Lubricant amount 13 g 9 g

Mobil Polyrex EM

Notes:

Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	30/03/2024				1/1	