

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE3 Three-Phase

Product code : 12861411

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/
T125 °C

Catalog # : E04518ET3YAX225SMF3W

Frame : 225S/M
Output : 45 kW (60 HP)
Poles : 4
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 86.4/49.7 A
L. R. Amperes : 631/363 A
LRC : 7.3
No load current : 36.0/20.7 A
Rated speed : 1482 rpm
Slip : 1.20 %
Rated torque : 214 ft.lb
Locked rotor torque : 250 %
Breakdown torque : 280 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 16.0 sq.ft.lb
Design : N

Locked rotor time : 16s (cold) 9s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 63.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 921 lb

Output	25%	50%	75%	100%				
Efficiency (%)	0.000	93.8	93.5	94.0	94.1	94.2	94.2	
	0.000	93.0	93.0	94.1	94.5	94.2	95.0	
	0.000							
Power Factor	0.00	0.00	0.70	0.65	0.80	0.77	0.84	0.82
	0.00	0.62	0.64	0.75	0.75	0.80	0.81	

Foundation loads
Max. traction : 1889 lb
Max. compression : 2728 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.9	5.9	5.9	5.0
	P2 (0,5;1,0)	5.0	5.0	5.0	4.3
	P3 (0,25;1,0)	5.0	5.0	5.0	4.2
	P4 (0,9;0,5)	2.8	2.8	2.8	2.4
	P5 (0,5;0,5)	1.9	1.9	1.9	1.6
	P6 (0,5;0,25)	1.2	1.2	1.2	1.1
	P7 (0,25;0,25)	0.9	0.9	0.9	0.7

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6314 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	14000 h	14000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

ATEX
Baseefa 10ATEX0192X
BAS21UKEX0284X
II 3G Ex ec IIC T3 Gc
II 3D Ex tc IIIB T125°C Dc
EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
OOO «НАННО ЛСВЭ»
IECEX

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	27/03/2024			
			Revision	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

Subject to change without notice

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

IECEX BAS 10.0099X
Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 3		Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				3 / 3	
Date	27/03/2024				