DATA SHEET



Three Phase Induction Motor - Squirrel Cage Customer Product line : W22 Tru-Metric IE2 Three-Phase Product code: 12324563 Frame : 32s (cold) 18s (hot) : 315S/M Locked rotor time Output : 250 HP (185 kW) Temperature rise : 80 K Poles Duty cycle : S1 : 4 Frequency : 50 Hz Ambient temperature : -20°C to +40°C Rated voltage : 380 V Altitude : 1000 m.a.s.l. Rated current : 338 A Protection degree : IP55 Cooling method : IC411 - TEFC L. R. Amperes : 2298 A LRC : 6.8 Mounting : B3L(E) : Both (CW and CCW) No load current : 102 A Rotation¹ Rated speed : 1485 rpm Noise level² : 71.0 dB(A) Slip : 1.00 % Starting method : Direct On Line Rated torque : 884 ft.lb Approx. weight3 : 2569 lb Locked rotor torque : 210 % Breakdown torque : 220 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 65.9 sq.ft.lb Design : N Output 25% 50% 75% 100% Foundation loads 95.1 94.5 95.1 94.7 95.6 95.5 95.5 95.6 Efficiency (%) Max. traction : 3467 lb 93.6 94.1 95.0 95.4 Power Factor 0.54 0.46 0.79 0.72 0.85 0.81 0.87 0.85 Max. compression : 6035 lb 0.47 0.72 0.83 0.86 Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) 4.9 4.8 5.0 P2 (0,5;1,0) 3.3 3.2 3.4 P3 (0,25;1,0) 2.5 2.5 2.6 Losses (%) P4 (0,9;0,5) 3.3 3.2 3.3 P5 (0,5;0,5) 1.9 1.8 1.9 P6 (0,5;0,25) 1.5 1.5 1.6 P7 (0,25;0,25) 8.0 0.8 8.0 Drive end Non drive end Bearing type 6319 C3 6316 C3 WSeal Sealing WSeal 10000 h Lubrication interval 8000 h Lubricant amount 45 g 34 g Lubricant type Mobil Polyrex EM Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1/1	