

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xdb IE2 Three-Phase

Product code : 12430295
Catalog # : E00718XP3YAX132MF3-W

Area classification : ZONA 1, GRUPO IIB, T4 (135 °C)

Frame	: 132S/M	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 7.5 kW (10 HP)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 14.8/8.52 A	Protection degree	: IP56
L. R. Amperes	: 107/61.4 A	Cooling method	: IC411 - TEFC
LRC	: 7.2	Mounting	: B3T
No load current	: 6.40/3.68 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1460 rpm	Noise level ²	: 56.0 dB(A)
Slip	: 2.67 %	Starting method	: Direct On Line
Rated torque	: 36.2 ft.lb	Approx. weight ³	: 246 lb
Locked rotor torque	: 200 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 1.25 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads				
Efficiency (%)	88.2	87.8	88.4	88.0	88.7	88.7	88.7	88.7	Max. traction : 466 lb
	87.4	88.2	87.7	88.5	89.0	90.2	89.0	90.2	
Power Factor	0.45	0.39	0.73	0.66	0.83	0.79	0.87	0.84	Max. compression : 712 lb
	0.35	0.37	0.61	0.63	0.75	0.76	0.81	0.83	

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6308 ZZ	6207 ZZ
Sealing	:	Oil Seal	Lip Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

EAC
EA3C RU C-BR.AA87.B.00379/20
1Ex db IIB T4 Gb X
ООО «НАННО ЦСВЭ»
IECEX
IECEX INE 22.0044X
Ex db IIB T4 Gb

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	27/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	150 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	27/03/2024				