DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer	:								
Product line	: W22 Tru-Metric IE3 Three-Phase			Product code : Catalog # :	11567172 11018ET3Y280S/M-W22				
Frame	: 280S/N	1	Locked	rotor time	· 48s (cold)) 27s (hot)			
Output	: 150 HF		ature rise	: 80 K	: 48s (cold) 27s (hot)				
Poles		Duty cy		: S1					
	: 4	Duty Cy	CIE	: -20°C to +40°C					
Frequency	: 50 Hz			t temperature					
Rated voltage	: 380 V	Altitude		: 1000 m.a	.S.I.				
Rated current	: 206 A		ion degree	: IP55					
L. R. Amperes	: 1566 A		method	: IC411 - T	EFC				
LRC	: 7.6	Mountir		: B3L(E)					
No load current	: 61.5 A	Rotatio	n¹	: Both (CW and CCW)					
Rated speed	: 1483 rp	Noise le	evel ²	: 69.0 dB(A)					
Slip	: 1.13 %		Starting	method	: Direct On Line				
Rated torque	: 531 ft.ll		. weight³	: 1808 lb					
Locked rotor torque									
Breakdown torque									
Insulation class	: F								
Service factor	: 1.25								
Moment of inertia (-	ff lh							
Design	: N	.11.10							
Output	25% 50%	75% 100%	Foundation	on loads					
Efficiency (%)	95.0 94.9 95.2 95.3		Max. trac						
	94.0 94.5 95.4 95.8								
		7 0.77 0.72 0.83 0.80 0.85 0.84 Max. compression 0.72 0.80 0.84		pression	: 4078 lb				
Losses at normative	e operating points (sp	eed:torque) in nerce	ntage of ra	ted output nower					
	P1 (0,9;1,0)	4.8		.0	4.3				
		3.5		9	3.2				
	P2 (0,5;1,0)								
	P3 (0,25;1,0)	2.9		5	2.7				
Losses (%)	P4 (0,9;0,5)	2.8		4	2.6				
	P5 (0,5;0,5)	1.7		.4	1.5				
	P6 (0,5;0,25)	1.2	1	.0	1.1				
	P7 (0,25;0,25)	0.7	C	.6	0.7				
	-	Drive end	Non drive end		1				
Bearing type		6316 C3		6316 C3	<u>4</u>				
Sealing		WSeal		WSeal					
Lubrication interval		10000 h		10000 h					
Lubricant amount	· .	34 g							
	•	_	34 g						
Lubricant type	·	IVIOI	obil Polyrex EM						
Notes:									
	This revision replaces and cancel the previous one, which				These are average values based on tests with sinusoidal				
must be eliminated.			power su	ipply, subject to th	ne tolerances stipu	ılated in NEMA			
(1) Looking the mot	or from the shaft end.		MG-1.						
	and with tolerance of								
	eight subject to change								
manufacturing proc									
(4) At 100% of full le									
Rev.	Chang	ges Summary	1	Performed	Checked	Date			
- '	2.101.18	,,				+			

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1 / 1	