

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE3 Three-Phase

Product code : 13840797

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/  
T125 °C

Catalog # : E03736ET3YAX200LF3-W

Frame : 200L  
Output : 37 kW (50 HP)  
Poles : 2  
Frequency : 50 Hz  
Rated voltage : 380/660 V  
Rated current : 69.8/40.2 A  
L. R. Amperes : 530/305 A  
LRC : 7.6  
No load current : 24.0/13.8 A  
Rated speed : 2965 rpm  
Slip : 1.17 %  
Rated torque : 87.9 ft.lb  
Locked rotor torque : 300 %  
Breakdown torque : 300 %  
Insulation class : F  
Service factor : 1.00  
Moment of inertia (J) : 5.62 sq.ft.lb  
Design : N

Locked rotor time : 19s (cold) 11s (hot)  
Temperature rise : 80 K  
Duty cycle : S1  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : B3T  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 72.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 551 lb

| Output         | 25%  |      | 50%  |      | 75%  |      | 100% |      |
|----------------|------|------|------|------|------|------|------|------|
| Efficiency (%) | 92.8 | 92.2 | 93.0 | 92.6 | 93.6 | 93.4 | 93.7 | 93.7 |
|                | 91.4 | 91.3 | 92.0 | 91.5 | 93.2 | 93.0 | 93.7 | 93.0 |
| Power Factor   | 0.49 | 0.44 | 0.74 | 0.69 | 0.83 | 0.79 | 0.86 | 0.84 |
|                | 0.39 | 0.42 | 0.63 | 0.68 | 0.76 | 0.78 | 0.82 | 0.83 |

Foundation loads  
Max. traction : 786 lb  
Max. compression : 1337 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

|            |                |     |     |     |     |
|------------|----------------|-----|-----|-----|-----|
| Losses (%) | P1 (0,9;1,0)   | 6.4 | 6.4 | 6.4 | 7.1 |
|            | P2 (0,5;1,0)   | 5.1 | 5.1 | 5.1 | 5.7 |
|            | P3 (0,25;1,0)  | 4.8 | 4.8 | 4.8 | 5.4 |
|            | P4 (0,9;0,5)   | 3.4 | 3.4 | 3.4 | 3.8 |
|            | P5 (0,5;0,5)   | 2.1 | 2.1 | 2.1 | 2.4 |
|            | P6 (0,5;0,25)  | 1.5 | 1.5 | 1.5 | 1.6 |
|            | P7 (0,25;0,25) | 1.0 | 1.0 | 1.0 | 1.1 |

|                      |   |                  |                      |
|----------------------|---|------------------|----------------------|
|                      |   | <u>Drive end</u> | <u>Non drive end</u> |
| Bearing type         | : | 6312 C3          | 6212 C3              |
| Sealing              | : | V'Ring           | V'Ring               |
| Lubrication interval | : | 15000 h          | 18000 h              |
| Lubricant amount     | : | 21 g             | 13 g                 |
| Lubricant type       | : | Mobil Polyrex EM |                      |

Notes:

ATEX  
Baseefa 10ATEX0192X  
BAS21UKEX0284X  
II 3G Ex ec IIC T3 Gc  
II 3D Ex tc IIIB T125°C Dc  
EAC  
TC RU C-BR.AA87.B.00977/22  
2Ex ec IIC T3 Gc X  
Ex tc IIIB T125°C Dc X  
ООО «НАННО ЛЦБЭ»  
IECEX  
IECEX BAS 10.0099X

| Rev.         | Changes Summary | Performed | Checked | Date |
|--------------|-----------------|-----------|---------|------|
|              |                 |           |         |      |
| Performed by |                 |           |         |      |
| Checked by   |                 |           |         |      |
| Date         | 27/03/2024      |           |         |      |

Page 1 / 3  
Revision

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Ex ec IIC T3 Gc  
Ex tc IIIB T125°C Dc

| Rev.         | Changes Summary |  | Performed     | Checked | Date     |
|--------------|-----------------|--|---------------|---------|----------|
|              |                 |  |               |         |          |
| Performed by |                 |  | Page<br>2 / 3 |         | Revision |
| Checked by   |                 |  |               |         |          |
| Date         | 27/03/2024      |  |               |         |          |

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

| ID | Application | Type                 | Quantity  | Sensing Temperature |
|----|-------------|----------------------|-----------|---------------------|
| 1  | Winding     | Thermistor - 2 wires | 1 x Phase | 140 °C              |
| 2  | Winding     | Thermistor - 2 wires | 1 x Phase | 155 °C              |

|              |                 |  |           |         |          |
|--------------|-----------------|--|-----------|---------|----------|
| Rev.         | Changes Summary |  | Performed | Checked | Date     |
|              |                 |  |           |         |          |
| Performed by |                 |  |           | Page    | Revision |
| Checked by   |                 |  |           | 3 / 3   |          |
| Date         | 27/03/2024      |  |           |         |          |