




Color: **Brown** 

UPC Code: 078477249703 Country Of Origin: Mexico



### **Available Colors:**







White

# 5821

Single Receptacle Outlet, Commercial Specification Grade, Smooth Face, 20 Amp, 250 Volt, Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - Brown

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

#### Technical Information

**AC Horsepower Ratings** At Rated Voltage: 2 HP **Electrical Specifications** 

Amperage: 20 A

**Current Limiting:** Full Rated Current Dielectric Voltage: Withstands 2000V

per UL498

Grounding: Self-Grounding

Pole: 2

Voltage: 250 VAC

Wire: 3

**Environmental Specifications** Flammability: Rated V-2 per UL 94 Operating Temperature : -40°C to 60°C

Material Specifications Body Material: Nylon Face Material: Nylon

Grounding Screw: Brass 8-32 **Line Contacts**: Brass Double Wipe .031 Thick

Terminal Screws: Brass 8-32 Yoke: Zinc-Plated Steel

Mechanical Specifications

Product ID: Ratings are permanently marked on device

Terminal Accom.: 14-10 AWG

Terminal ID: Brass-Hot, Green-Ground,

White-Neutral

Termination : Side Wire

**Product Features** Amperage: 20 A Body Material: Nylon

Color: Brown

Device Type: Single Receptacle Outlet

Face Material: Nylon Feature 4: Smooth Face

Grade: Commercial Specification Grade

**Grounding:** Self-Grounding

**NEMA: 6-20R** Pole: 2

Standards and Certifications: UL/CSA

Strap Material: Steel Termination: Side Wire Voltage: 250 VAC Warranty: 10-Year Limited

Wire: 3

Standards and Certifications

**ANSI:** C-73

CSA C22.2 No. 42: File 152105


**NEMA: WD-1 & WD-6** 

**NOM: 057** 


UL Fed Spec WC-596: File E13399

UL498: File E13399

## Dimensional Diagram



## Wiring Diagram



6-20R

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Telephone: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

### Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

